



NOTES:

1. REPAIRED SURFACE TO BE AT LEAST AS GOOD AS ORIGINAL SURFACE. FINISHED ASPHALT PATCH SHALL BE OF MATERIAL EQUIVALENT TO EXISTING.
2. ASPHALT TO BE PLACED WITHIN 10 WORKING DAYS OF UTILITY INSTALLATION OR REPAIR. (STONE TO BE BROUGHT UP TO STREET SURFACE AND MAINTAINED DURING 10 DAY INTERIM.)
3. NEATLY SAW CUT ALL ASPHALT EDGES PRIOR TO PLACING ASPHALT PATCH.
4. TRAFFIC SAFETY MEASURES ARE REQUIRED IN ACCORDANCE WITH THE LATEST VERSION OF THE VA WORK AREA PROTECTION MANUAL.
5. DURING COLD WEATHER, COLD MIX TO BE USED AS TEMPORARY MEASURE. PERMANENT SM-2A PAVING TO BE PLACED WITHIN 3 WEEKS OF START UP OF HOT MIX PLANTS. CHECK STONE AND REFILL/TAMP AS NECESSARY, AT LEAST WEEKLY, UNTIL RESURFACED.

**AUGUSTA COUNTY SERVICE AUTHORITY
VERONA, VIRGINIA**

SCALE: NTS

DRAWN BY: ACSA

DATE: NOV. 2014

REVISED: MAR. 2021

**TYPICAL PAVEMENT PATCH
FOR PRIVATE PAVED ROADS**

DRAWING NUMBER: G-7

PAGE: 1 OF 1